

For faster delivery call Customer Service.

Note: Discounts are based on a complete Digi-Stem System (Meter + Probe = 1 unit).
 Discounts are also applied to Probes and Meters separately, but may not be combined for quantity discounts.

DSTA200, DSTA300, DSTA310, DSXA300 SERIES RIGID PROBE ORDER GUIDE					
Code	Select Grounded or Ungrounded Series (Select One)				
DSTPA	Grounded Stem (for DST Display Meters)				
DSXPA	Ungrounded Stem (for DSX Display Transmitters)				
Code	Select Rigid Stem Process Connection (Select One)				
12	1/2" NPT Fitting (Standard)				
13	3/4" NPT Adapter				
20	1-1/4" x 18 NEF2 Thermowell Adapter				
30	1-1/2" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)				
31	2" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)				
32	2-1/2" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)				
33	3" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)				
50	Union Thermowell Fitting, 1-1/4" x 18 NEF2				
Code	Select Rigid Stem Type (Select One)				
1	Cut to Length (User), 12" Standard (add in 6" increments thereafter)				
2	Cut to Length (Factory)				
3	Brazed				
4	Welded (included in all 3-A Connections)				
5	Spring Loaded (not available with Connection Code 50)				
Code	Select Rigid Stem Material (Select One)				
1	304 SS, Temp Rating 400°F (204°C) (Standard)				
2	316 SS, Temp Rating 400°F (204°C)				
3	316 SS, Temp Rating 900°F (482°C)				
4	304 SS, Temp Rating 900°F (482°C)				
Code	Select Rigid Stem Tip Diameter (Select One)				
2	1/4" Diameter (Standard)				
3	3/8" Diameter with Stem Adapter				
4	1/2" Diameter with Stem Adapter				
5	7/16" Diameter with Stem Adapter, Tapered				
6	7/16" Diameter with Stem Adapter, Straight				
Code	Specify Rigid Stem Length				
01-12	1" to 12" (12" Standard)	Specify exact length desired in inches: _____			
13-99	13" to 99", add per inch over 12".	Specify exact length desired in inches: _____			
XXX	100" and over, add per inch over 99".	Specify exact length desired in inches: _____			
01 = 1 inch, 02 = 2 inches, 03 = 3 inches, etc. Fractional Lengths available: A = 1/4", B = 1/2", C = 3/4" Example: 08C = 8-3/4".					
DS _____					
Series	Process Connection	Stem Type	Stem Material	Stem Tip Diameter	Stem Length

Note: All Palmer Wahl Sanitary products have a surface finish (Ra) of 32 µ inch (.8µm) or better. Other finishes, including Electropolishing are available as options, priced on request.

Note: Re-certify/Recalibrate - no discount

Prices, Lead Times and Specifications subject to change without notice.

DSTA200, DSTA300, DSTA310, DSXA300 SERIES REMOTE PROBE ORDER GUIDE						
Code	Select Grounded or Ungrounded Series (Select One)					
DSTPA	Grounded Stem (for DST Display Meters)					
DSXPA	Ungrounded Stem (for DSX Display Transmitters)					
Code	Select Remote Stem Type (Select One)					
40	PVC - Temperature Rating 221°F (105°C)					
41	Teflon Covered					
42	Armored					
44	Coiled (TPE Insulated only)					
Code	Select Remote Cable Length (Select One)					
01-06	Codes 40, 41 or 42, 6 foot length Standard (Code 06) (01 = 1 ft, etc.)				Specify exact length desired _____	
07-99	Codes 40 or 41, PVC or Teflon, 7 to 99 ft - add per ft over 6' (07 = 7 ft, etc.)				Specify exact length desired _____	
07-99	Code 42, Armored, 7 to 99 ft - add per foot over 6' (07 = 7 ft, etc.)				Specify exact length desired _____	
01	Code 44, Coiled only, (5:1 Expansion Ratio) 1 foot length Standard (Code 01)				Specify exact length desired _____	
02-04	Code 44, Coiled only, add per ft over 1 ft (02 = 2 ft, etc.)				Specify exact length desired _____	
Code	Select Remote Stem Material (Select One)					
1	304 SS, Temp Rating 400°F (204°C) (Standard)					
2	316 SS, Temp Rating 400°F (204°C)					
3	316 SS, Temp Rating 900°F (482°C)					
4	304 SS, Temp Rating 900°F (482°C)					
Code	Select Remote Stem Tip Diameter (Select One)					
2	1/4" Diameter (Standard)					
3	3/8" Diameter with Stem Adapter					
4	1/2" Diameter with Stem Adapter					
5	7/16" Diameter with Stem Adapter, Tapered					
6	7/16" Diameter with Stem Adapter, Straight					
8	TC817 Style Piercing Probe w Handle (Note: if ordering this, Part Number ends here)					
Code	Specify Remote Stem Process Connection (Select One)					
0	No Stem Connection or Fitting					
1	1/2" NPT Compression					
2	1/2" NPT Compression with 3/4" NPT Adapter					
3	1-1/4" x 18 NEF2 Thermowell Adapter					
5	Union Thermowell Fitting, 1-1/4" x 18 NEF2					
6A	1-1/2" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)					
6B	2" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)					
6C	2-1/2" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)					
6D	3" Diameter; 3-A Sanitary Flange, Welded (Stem Material Codes 2 & 3 only)					
7	1/2" NPT Brazed					
8	1/2" NPT Welded (included in all 3-A Connections)					
9	1/2" NPT Spring Loaded					
Code	Specify Remote Stem Length (Select One)					
01-12	1" to 12" (12" Standard)				Specify exact length desired _____	
13-99	13" to 99", add per inch over 12".				Specify exact length desired _____	
XXX	100" and over, add per inch over 99".				Specify exact length desired _____	
' 01 = 1 inch, 02 = 2 inches, 03 = 3 inches, etc. Fractional Lengths available: A = 1/4", B = 1/2", C = 3/4" Example: 08C = 8-3/4".						
DS_____						
Series	Stem Type	Cable Length	Stem Material	Stem Tip Diameter	Process Connection	Stem Length

Note: All Palmer Wahl Sanitary products have a surface finish (Ra) of 32 μ inch (.8μm) or better. Other finishes, including Electropolishing are available as options, priced on request.