



RG58 Flexible Coax Cable Black PVC Jacket

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	DC		1,000	MHz
Impedance		50		Ohms
Velocity of Propagation		66		%
Operating Voltage (AC)			1,900	Vrms
Nominal Capacitance		30.8		pF/ft
		[101.05]		[pF/m]

Performance by Frequency Band

Description	F1	F2	F3	F4	F5	Units
Frequency	10	100	1,000			MHz
Attenuation, Typ	1.4 4.59	4.9 16.08	20 65.62			dB/100ft dB/100m

Mechanical Specifications

Diameter 0.195 in [4.95 mm] Weight 0.025 lbs/ft [0.04 Kg/m]

Min. Bend Radius (Installation) 0.787 in [19.99 mm]

Construction Specifications

Description	Material and Plating	Diameter
Inner Conductor	Copper, Tin, 7 Strands	0.136 in [3.45 mm]
Conductor Type	Strands	
Dielectric	PE	0.116 in [2.95 mm]
First Shield	Tinned Copper Braid	
Jacket	PVC, Black	0.195 in [4.95 mm]

Environmental Specifications Temperature

Operating Range

-40 to +80 deg C

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

RoHS Compliant

REACH Compliant 12/17/2015

Plotted and Other Data

Notes:



Configuration:

- Flexible Cable
- 1 Shield(s)

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





RG58 Flexible Coax Cable Black PVC Jacket from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order


Click the following link to obtain additional part information: RG58 Flexible Coax Cable Black PVC Jacket RG58CU

URL: https://www.fairviewmicrowave.com/rg58-flexible-coax-cable-pvc-jacket-rg58cu-p.aspx

				ave reserves the rig				
				w Microwave does r				
				y particular purpose	, and Fairvie	ew Microwa	ve does not assun	ne any liability
arising ou	t of the use of ar	ny part or do	cument	tation.				







FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
RG58 Flexible Coax Cable Black PVC Jacket	DWG NO RG58CU			CAGE CODE 3FKR5		
	CAD FILE 120315	SHEET	SCALI	E N/A	SIZE A	5568