

Range XXL :	XXL01	XXL01.5	XXL01.8	XXL02.7	XXL03	XXL04.5	XXL08	XXL12	XXL15
									

Performances :

Temperature range :		Température ambiante + 20 °C à 200 °C							
Standard maximum temperature :		200 °C							
Homogeneity at 105 °C :	± °C	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0	< 2.0
Temporal stability :	± °C	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2

Chamber dimensions :

Chamber volume :	dm ³	1000	1500	1800	2700	3000	4500	8000	12000	15000
Width :	mm	1000	1000	1000	1000	1500	1500	2000	2000	2500
Depth :	mm	1000	1000	1000	1800	1500	2000	2000	3000	3000
Height :	mm	1000	1500	1800	1500	1500	1500	2000	2000	2000

External dimensions:

External volume :	m ³	3.39	4.87	5.54	7.57	9.09	11.29	17.58	25.28	29.86
Width :	mm	1535	1580	1556	1570	2056	2056	2559	2505	2900
Depth :	mm	1559	1561	1559	2362	2070	2570	2578	3608	3607
Height :	mm	1415	1974	2283	2041	2136	2136	2665	2797	2855

Autres informations :

Number of doors :		1	1	1	1	2	2	2	2	2
Internal air flow :	m ³ /h	1800	2500	2500	3250	4000	4000	6000	8000	12000
Door window W x H (option) :	mm	350x550	400x800	400x800	400x800	180x350 (x2)	180x350 (x2)	400x800 (x2)	400x800 (x2)	400x800 (x2)
Weight :	kg	500	620	680	850	980	1050	1300	1700	2400

Electrical data :

Heating power 200° :	Watts	12000	15000	18000	21000	24000	27000	36000	45000	54000
Power supply :	Volts	400V ~3P 50Hz 20A	400V ~3P 50Hz 25A	400V ~3P 50Hz 32A	400V ~3P 50Hz 40A	400V ~3P 50Hz 40A	400V ~3P 50Hz 50A	400V ~3P 50Hz 63A	400V ~3P 50Hz 80A	400V ~3P 50Hz 100A

We reserve the right to make any technical modification without prior notice.