

## Tilted-Arm Screen Printing Machine(GW-6090X)



Worktable size: 700\*1100mm



Enquiry



Back

Describe

Video

### PVC Sheet Electric Flat Silk Screen Printing Machine

#### Function:

- 1.Tilted-arm structure, The forward/backward action of printing head is driven by electromotion
- 2.SCM controlled circuit,printing and screen plate up/down adopts independent driver source
- 3.Frequency conversion motor drives printing knife rest, magic eye controls strock distance, independent adjustment
- 4.There are average air intakes on high -hardness Worktable,
- 5.Power vacuum adsorption,make sure accurate color registration
- 6.There are three kinds of models,such as manual.semi-automatic and full-automatic,printing indirect time is controlled by figure
- 7.independently designing machine head up/down equipment,it is convenient to replace scraper,ink covering blades and frame and easy to clean screen frame
- 8.Double guide rod left/right screen arm, and equipt plate distance adjustale equipment, easily adjust

#### Collocate introduction

- 1.machine control adopts Germany Philips PNX SCM controller,control plate with button
- 2.Circuit adopts Japan OMRON relay,China CHNT AC Electromagnetic Contactor and Taiwan RIKO photocell eye switch
- 3.Printing adopts Taiwan ABBA linearity slide rail and Chenggang gear decelerate motor,Danmark HOLIP tansducer printing drive
- 4.Printing scraper and ink covering blades adopts Italy EASUN pneumatic component control
- 5.Printing worktable adopts special structure and special material.

#### Technical parameter:

- 1.Max.printing area:600\*900mm
- 2.Max.printing speed:1000PCS/Hr
- 3.Power:220V/110V 50-60MHZ | 200W
- 4.Air pressure:5-7bar
- 5.Worktable size:700\*1100mm
- 6.Max.sreen frame size: 750\*1300MM
- 7.Max.workpiece height:50mm