

P 6000 Inox (600966000) Garden Pump (220-240 V / 50 Hz); Cardboard box

Order no. 600966000 EAN 4007430240538



Product may differ from Image





- For garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Metabo pump protection: automatic dry-run protection with LED display to protect the pump and high user safety
- Multi-level pump running gear for high performance and low-noise operation
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Durable stainless steel pump housing
- Separate water filling opening for simple operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- Rubberised feet for low-noise and low-vibration operation
- Ergonomic handle for comfortable transport
- For garden irrigation with 1 to 4 sprinklers

www.metabo.com 1/2



| Technical data | |
|------------------------------|--|
| Characteristics | |
| Rated input power | 1300 W |
| Maximum delivery rate | 6000 l/h / 1585 gal/h |
| Maximum delivery height | 55 m / 180 ft |
| Maximum pressure | 5.5 bar / 79.8 psi |
| Maximum suction height | 8 m / 26 ft |
| Suction port | 1" female thread |
| Discharge port | 1" female thread |
| Pump housing | Stainless steel |
| Protection type IP | IP X4 |
| Drive shaft | Stainless steel |
| Number of impellers | 5 |
| Dimensions | 470 x 222 x 303 mm / 18 1/2 x 8 3/4 x 11 15/16 " |
| Weight | 12.7 kg / 28 lbs |
| Cable length | 1.5 m / 5 ft |
| Noise emission | |
| Sound pressure level | 63 dB(A) |
| Sound power level (LwA) | 75.9 dB(A) |
| Uncertainty of measurement K | 2.3 dB(A) |

Scope of delivery

Fabric Sealing Tape

www.metabo.com 2/2