

**TS 216 Floor (600676000) Table Saw**  
(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600676000  
EAN 4007430246943



Product may differ from Image



- Light table saw, also suitable for one-handed transport
- Anti-twist tubular frame construction for highest demands on the building site and during installations
- Cables and all add-on components for transport can be stored on the casing
- Powerful motor with electronic overload protection
- Motor brake for quick stop of the saw blade in 3 seconds
- Restart protection: prevents unintentional start-up after power supply interruption
- Soft start for long service life of motor and drive
- Precise parallel guide with double clamping and quick fastening
- Precise saw blade inclination via gear guide
- Automatic resetting to 0 – 45 ° after undercuts
- Easy saw blade change with spindle lock
- Splitting wedge can be lowered without tools for hidden cuts and transport
- Precise, extendable table width extension for extra large working surfaces
- Dual port dust extraction for low dust emission

## Technical data

### Characteristics

|   |   |
|---|---|
| Dimensions  | 670 x 650 x 355 mm / 2.2 x 2.2 x 1.2 ft |
| Max. support surface                              | 780 x 930 mm / 30 1/2 x 36 1/2 "        |
| Working height                                    | 355 mm / 14 "                           |
| Cutting height                                    | 0 - 63 mm // 0 - 2 1/2 "                |
| Maximum cutting height 90/45°                     | 63 / 43 mm // 2 1/2 / 1 11/16 "         |
| Maximum cutting width at parallel guide/rip fence | 425 mm / 16 3/4 "                       |
| Maximum material width at mitre fence             | 165 mm / 6 1/2 "                        |
| No-load speed                                     | 5000 rpm                                |
| Cutting speed                                     | 57 m/s / 187 ft/s                       |
| Saw blade   | 216 x 30 mm / 8 1/2 x 1.181 "           |
| Saw blade swivel range                            | -1.5 - 46.5 °                           |
| Rated input power                                 | 1500 W                                  |
| Weight  | 23.2 kg / 49 lbs kg                     |
| Cable length                                      | 3 m / 10 ft                             |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 89 dB(A)  |
| Sound power level (LwA)      | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Carbide saw blade with alternately bevel-ground tips (30 teeth)  
 Table Length Extension  
 Table width extension (left)  
 Table width extension (right)  
 Chip and Dust Extraction Unit  
 Push stick  
 Parallel Guide / Rip Fence  
 Mitre Fence