



GPRINTER ISH58

**/ Multiple interfaces,
with cloud print service**

**/ Support Smart Speak
function, easy to operate**

**/ Small and exquisite body,
eye catching appearance**

**/ Touch panel design,
waterproof, damp-proof
and durable**

**/ Support application
development to promote
business rapidly**



Touch Buttons



Durable rubber roller

Zig-zag paper tear



Supports a variety of takeaway software that prints via Bluetooth connection



PRINT	
Method	Direct Thermal Line
Resolution	203dpi
Print Speed	70mm/s
Interface and function	USB+Bluetooth: Support + 7 Android apps (Multi-Device) / + 7 Apple apps (Single Device)
	USB+WiFi: Support AP, STA, AP + STA three modes
	USB+Ethernet: USB2.0 + 100M Ethernet
	USB+GPRS Cloud: Support Mobile 2G
	Unicom 2G standard SIM card. Voice Service optional
	USB+WiFi Cloud: WiFi cloud printing, smart distribution network. Voice Service optional
Print Width	48mm Max
Line Spacing	3.75mm (Line Spacing can be adjusted by command)
Column	Font A-32 Column / Font B-43 column / simplified
Memory	FLASH: 60KB
BARCODE & GRAPHIC	
Program	ESC / OPOS
Print head temperature Detection	Thermal sensitive resistance
Paper Sensor	Photoelectricity sensor
Code Page	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 / WestEurope / Greek / Hebrew
	EastEurope / Iran / WPC1252 / PC866 / PC852 / PC858 / IranII / Latvian / Arabic
	PT151, 1251 / PC747 / WPC1257 / Vietnan / PC864 / PC1001 / Uyгур / Thai
Barcode Type	UPCA, UPCE, JAN13(EAN13), JANA(EAN8), CODE39, ITF, CODABAR, CODE93, CODE128, QRCODE
Character Size	ANK Font .Font A: 1.5x3.0mm (12x24 dots) Font B: 1.1x2.1mm (9x17 dots)
	Simplified / Traditional Chinese: 3.0x3.0 (24x24 dots)
Character enlargement / rotation	1-10 times enlargement in horizontal and vertical
	Character enlargement / rotation directions; Rotation printing (0°, 90°, 270°)
Graphics	Black and white PCX, BMP files can be downloaded into FLASH or DRAM
MEDIA	
Paper Type	Thermal Paper
Paper Width	57.5±0.5mm
Paper Roll Diameter	60mm
Paper out method	Top feed

POWER	
DC Input	DC 9V-2A
Out put	DC 12V-1A
Power Supply	Input: AC100V-240V, 50-60Hz Output: DC 9V-2A
ENVIRONMENT	
Operation Condition	Temperature: 5~45° Humidity: ≤ 93%RH
Storage Condition	Temperature: 5~45° Humidity: ≤ 93%RH
PHYSICAL PROPERTIES	
Printer Dimensions	150x123x102
Weight	620g
RELIABILITY	
Mechanism	50KM
SOFTWARE	
Driver	Win9X / WinME / Win2000 / WinNT / WinXP, WinVista, Win7, Win8, Win10, Linux
Tool	GpTools (Android), GprinterSetTool (Windows)
Development Support	Android SDK, iOS SDK, Windows DLL

/ EMAIL
info@delfi.com.vn

/ HOTLINE
0948 490 070

/ WEBSITE
delfi.com.vn

