

*C*printer®



BABY280(PT-280)

58mm mobile printer
Wifi and Bluetooth

Features

- Drop in paper loading, easy operation;
- Thermal Paper: width 58mm, diameter 50mm, thickness 0.06~0.08mm;
- Support to print receipt during charging the battery;
- Lithium battery: 1900mA/7.4V;
- Power adapter: 8.5V-2A, AC100-240VLow-power mechanism;
- USB+Bluetooth port, support Android and iOS and Windows system;
- Bluetooth: BT3.0 and BLE4.0;
- Support 1D barcode, QR barcode;
- Support for printing different density bitmap and download graphics;
- Support parallel port, serial port, USB port, Ethernet port ,bluetooth, USB+Wi-Fi+Blueooth.

Specification

Print method	Direct thermal line
Print width	48mm
Dot density	384dot/line
Print speed	60mm/s

Interface	USB+WIFI / USB+Bluetooth / USB+WiFi+Bluetooth	
Paper width	58mm	
Paper diameter:	50mm	
Paper thickness	0.06~0.08mm	
Print commands	Compatible with ESC/POS	
Fonts	GB18030, Big5, Japanese, Korean	
Character Size	ANK Font: FontA: 12X24dots	
Barcode mode	FontB: 9X17dots	
	Simplified/Traditional Chinese Character, Japanese, Korean: 24X24dots	
	UPC-A、UPC-E、EAN(JAN)13、EAN(JAN)8、CODE39、CODABAR、ITF、CODE93、CODE128	
Data Buffer	4K bytes	
NV Flash Buffer	60K bytes	
Dimension	148.5*86*58.5mm	
Weight	288g (Battery: 98g)	
Power adaptor	input: AC220V output: DC8.5V/2A	
Lithium battery	1900mAh/7.4V	
Charge period	2.5h-3h	
Work environment	Temperature: 5~45°C, Humidity: 10~80%	
Storage environment	Temperature: -10~50°C, Humidity: 10~90%	
Mechanism Reliability	50KM	
Others	Driver	Android, iOS, (Win9X/Win ME/Win2000/WinNT/WinXP, WinVista, Win7, Win8,)
Paper supply method	Drop-in paper load	