

SCT-5545TBH High speed side sealing and shrinkage packing machine



Technical characteristics

SCT-5545TBH high speed edge sealing packer can be used to automatically shrink the product online, using optoelectronic to detect the product automatically. Two modes of automatic feeding or manual feeding can be selected, the folding film is used and the other three sides can be sealed.

1. according to the different configuration of the equipment and the different characteristics of the

product, the packaging speed can reach 20-45 pieces / minute.

- 2. The constant temperature heating sealing system can be used to seal the shrinkages of various industrial standards such as PE and POF. The sealing is strong and beautiful. It is especially suitable for POF film sealing. The products with different sizes and sizes can be adjusted with handwheel only. It is more reliable and easier to operate.
- 3. variable speed front end feeding system and storage platform at the rear end make the whole machine action truly high-speed and unmanned automatic operation.
- 4. the machine adopts the most advanced PLC programmable controller, with safety protection and alarm device, and the sealing and cutting system can make the sealing action continuously and smoothly, without replacement, the maintenance operation is very simple.
- 5. Feeding length control is combined with electric eye detection and timer to control the length of the film accurately, so that the shrinkage effect can be controlled more easily.
- 6. Add two sets of electric eye in horizontal and vertical electric eye to facilitate switching selection. For thin or small package, seal packaging can be done easily.
- 7. Automatic coiling waste is controlled by a single motor. It will not be too loose or too tight.
- 8. according to customer needs, add automatic blowing function.
- 9. According to the needs, the front power feeding line and the rear end powerless storage platform can be selected.

Scope of application

It is suitable for CD, DVD, cosmetics, electronic products, printing, color box, card, photo album, picture frame, frame and so on. It is suitable for batch production.

parameter:

•		
Product model	SCT-5545TBH	SCT-5030LX
Outer size	L2050×W1580×H1740mm	L1800×W1000×H1350mm
Maximum packing size	L Unlimited×W300×H150	L500×W400×H250mm
Cutters size	500mm	
Packaging speed	20 ~ 60Piece / minute	2500-3500/h
Net weight	800 kg	650KG
power	3 kw	16KW
Power Supply	3φ220V/380V 50/60Hz	3φ380V 50/60Hz
air source	5.5 kg/cm ²	